



APPROVAL OF MANUFACTURER CERTIFICATE

Certificate No:
AMMM00002W8
Revision No:
1

This is to certify:

That

Härterei Carl Gommann GmbH
Dreielstr. 29, 42855 Remscheid,
Germany

is an approved manufacturer of
Heat treatment

in accordance with

DNV rules for classification – Ships
DNV class programme – DNV-CP-0351 Manufacture of heat treated products - heat treatment workshop

and the following particulars:

Application area	Heat treatment workshop
Heat treatment process	Gas nitriding
Product type	Forging, Gearing, Machinery Equipment etc.
Steel type	See page 2
Max. weight	See page 2
Remarks	Approved as Independent Heat Treatment Company

Manufacturer(s) approved by this certificate is/are accepted to deliver according to DNV GL, DNV and GL rules.
Materials to be applied to DNV classed object shall fulfill the material requirements in the applicable DNV class rules.

Issued at **Hamburg** on **2024-07-17**

This Certificate is valid until **2027-08-16**.

DNV local unit: **Essen**

Approval Engineer: **Andrzej Otrebski**



for **DNV**

This document has been digitally signed and will
therefore not have handwritten signature

Stefan Röhr

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: AM 311

Revision: 2022-12

www.dnv.com

Page 1 of 2

Particulars of the approval

Approval scope for Independent Heat Treatment Company

Item	Description
Product type	Forging, Gearing, Machinery Equipment etc.
Heat Treatment Type	Gas nitriding
Steel Type	Non-alloy and low-alloy steels
Max. Dimensions	Diameter: max. 3 900 mm Length: max. 8 400 mm
Max. Weight	100 t